


| Main technical indicators(主要技术指标) |                                                                                                                    |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------|
| 1.Mating (插拔次数)                   | 5000                                                                                                               |
| 2.Working Temperature (温度)        | -55~+150℃                                                                                                          |
| 3.IP Rating (防护级别)                | IP 54                                                                                                              |
| 4.Diameter of socket end(插合端直径)   | φ1.3                                                                                                               |
| 5.Testing Voltage (测试电压)          | 1850V                                                                                                              |
| 6.Working Voltage (工作电压)          | 1850V                                                                                                              |
| 7.Rated Current (额定电流)            | 15A                                                                                                                |
| 8.Shell material(壳体材质)            | Brass (chromium plating) shell and chuck nut/( nickel plating) pin sleeve and middleware/黄铜(镀铬)外壳和夹头螺母/(镀镍)插销套和中间件 |
| 9.Pin Material(插针材料)              | Copper alloy gold plating(铜合金镀金)                                                                                   |
| 10.Insulator material(绝缘体材质)      | PPS                                                                                                                |


| Sum up(总结)                  |                                                                                                                                     |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Series(系列)                  | B                                                                                                                                   |
| Shell style/model (外壳样式/型号) | TEG: Straight plug, cable collet, front seal and nut for fitting a bend relief (IP 54 when mated)<br>直塞、电缆夹头、前密封件和用于安装弯曲凸起(配对时IP54) |
| Button (按键)                 | A button(一个按键)                                                                                                                      |
| Termination type (终止类型)     | Male solder(公焊锡)                                                                                                                    |
| Line diameter awg(线材直径)     | 28-20AWG                                                                                                                            |
| Cable diameterφ (电缆直径)      | φ4.3-5.2MM                                                                                                                          |
| Matching parts(配件)          | ZGG.2B.P04.CLL                                                                                                                      |

| Location pin combination(定位销组合) |                                      |           |                         |
|---------------------------------|--------------------------------------|-----------|-------------------------|
| (编号)<br>Nunder                  | Number of<br>positioning pins(定位销数量) | Angle(角度) | Series(系列)-2B           |
| G                               | One(1)                               |           | (Zero degrees)0°        |
| A                               | Two(2)                               | A         | Thirty degrees(30°)     |
| B                               | Two(2)                               |           | Forty-five degrees(45°) |
| C                               | Two(2)                               |           | Sixty degrees(60°)      |
| D                               | Two(2)                               | γ         | 95 degrees (95°)        |
| E                               | Two(2)                               | β         | 120 degrees(120°)       |
| F                               | Two(2)                               |           | 145 degrees(145°)       |
| J                               | Two(2)                               | A         | 37.5degrees(37.5°)      |
| K                               | Two(2)                               |           | 52.5degrees(52.5°)      |
| L                               | Two(2)                               | γ         | Seventy degrees(70°)    |

|        | A      | B      | C√     | ANGLE   |       |
|--------|--------|--------|--------|---------|-------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1° |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5° |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |       |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |       |




|    | A      | L      | M      | S1    | S2     |
|----|--------|--------|--------|-------|--------|
| MM | φ16.5  | 48     | 36     | 13.0  | 12     |
| in | 0.6496 | 1.8898 | 1.4173 | 0.512 | 0.4725 |



Welded surface  
(焊接面)



Solder core  
(焊接型公胶芯)



Positive view  
(正视图)

TE G. 2B. P04.C L A D 52 H

Model(型号)

Positioning pin(定位销)

Series(系列)

Needle core configuration(针芯配置)

Outer casing(外壳)

Insulator(绝缘体)

Needle core(针芯)

Type of clamp(线夹类型)

Cable diameter(电缆直径)

SH means a sheath type, not a cover type.  
(H表示护套型, 不表示为不带护套型)

|                                  |  |          |                                      |               |          |                                         |
|----------------------------------|--|----------|--------------------------------------|---------------|----------|-----------------------------------------|
| DESIGNED(设计)                     |  | DATE(日期) |                                      | SCALE(比例)     | N/A(不适用) | MODEL TYPE<br>型号类型: TEG.2B.P04.CLAD.52H |
| CHECKED(校对)                      |  | DATE(日期) |                                      | VIEW(视图)      |          | PART NO. 2B4-core plug<br>名称: 2B4芯插头    |
| APPROVED(审核)                     |  | DATE(日期) |                                      | UNIT(单位)      | MM       | DWG NO.:                                |
| REVISIONS                        |  |          |                                      | MATERIAL (材料) |          |                                         |
| www.helloxkb.com www.helloxkb.cn |  |          | XKB INDUSTRIAL PRECISION CO.,LIMITED |               |          | WEIGHT(重量) SHEET(表) REVISION(修订)        |
|                                  |  |          |                                      |               |          | 1/1 A0                                  |