

1.View and size(视图及尺寸)


| Main technical indicators(主要技术指标) |                                                                                                                           |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| 1.Mating (插拔次数)                   | 5000                                                                                                                      |
| 2.Working Temperature (温度)        | -55~+150 ℃                                                                                                                |
| 3.IP Rating (防护级别)                | IP 50                                                                                                                     |
| 4.Diameter of socket end(插合端直径)   | ø0.9MM                                                                                                                    |
| 5.Vtest (AC) /测试电压(交流)            | 1500V                                                                                                                     |
| 6.Vtest (DC) /测试电压(直流)            | 2100V                                                                                                                     |
| 7.Rated Current (额定电流)            | 10A                                                                                                                       |
| 8.Shell material(壳体材质)            | Brass (chrome plated ) shell and collet nut, nickel plated brass latch sleeve and mid pieces<br>/黄铜（镀铬）外壳和夹头螺母，镀镍黄铜锁套和中间件 |
| 9.Pin Material(插针材料)              | Copper alloy gold plating(铜合金镀金)                                                                                          |
| 10.Insulator material(绝缘体材质)      | PPS                                                                                                                       |

| Sum up(总结)                 |                                                                           |
|----------------------------|---------------------------------------------------------------------------|
| Series(系列)                 | S                                                                         |
| Shell style/model（外壳样式/型号） | TFF: Straight plug, non-latching, cable collet<br>/直插头，非闭锁，电缆夹头           |
| Button（按键）                 | Hermaphroditic keying (half moon insert) with male pin 1/带公销1的公母键控（半月形插入） |
| Termination type（终止类型）     | Male solder(公焊锡)                                                          |
| Line diameter awg(线材直径)    | 30AWG-22AWG                                                               |
| Cable diameterø（电缆直径）      | ø2.3-3.2MM                                                                |
| Matching parts(配套零件)       | ZRA.0S.P02.CLL                                                            |


| Sum up(总结)                |                                                       |
|---------------------------|-------------------------------------------------------|
| Humidity (max)/湿度最大       | <=95% [at 60 deg C /140 F]<br>/ <=95%[在60摄氏度/140摄氏度时] |
| Vibration/震动              | 15g [10 Hz - 2000 Hz]                                 |
| Shock Resistance/抗冲击性     | 100 g [ 6 ms]                                         |
| Climatical Category /气候类别 | 50/175/21                                             |
| Salt Spray Corrosion/盐雾测试 | >48 hr />48 小时                                        |

|        | A      | B      | C√     | ANGLE   |       |
|--------|--------|--------|--------|---------|-------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1° |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5° |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |       |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |       |

| DESIGNED (设计)                    |  | DATE(日期) |                                      | SCALE(比例) | N/A(不适用)                                                                              | MODEL TYPE<br>型号类型: TFF.0S.P02.CLAC.32 |
|----------------------------------|--|----------|--------------------------------------|-----------|---------------------------------------------------------------------------------------|----------------------------------------|
| CHECKED (校对)                     |  | DATE(日期) |                                      | VIEW(视图)  |  | PART NO. 0S2-core plug<br>名称: 0S2芯插头   |
| APPROVED (审核)                    |  | DATE(日期) |                                      | UNIT(单位)  | MM                                                                                    | DWG NO.:                               |
| REVISIONS                        |  |          | MATERIAL (材料)                        |           |                                                                                       |                                        |
| www.helloxkb.com www.helloxkb.cn |  |          | XKB INDUSTRIAL PRECISION CO.,LIMITED |           |                                                                                       | WEIGHT(重量) SHEET(页) REVISION(修订)       |
|                                  |  |          |                                      |           |                                                                                       | 1/1 A0                                 |



|    | A    | L    | M      | S2   |
|----|------|------|--------|------|
| MM | 9    | 34.5 | 24.5   | 6.5  |
| in | 0.35 | 1.36 | 0.9600 | 0.26 |



Welded surface  
(焊接面)



Solder core  
(焊接型公胶芯)

|                                 |                         |
|---------------------------------|-------------------------|
| Model(型号)                       | TFF. 0S. P02.C L A C 32 |
| Series(系列)                      |                         |
| Needle core configuration(针芯配置) |                         |
| Outer casing(外壳)                |                         |
| Insulator(绝缘体)                  |                         |
| Needle core(针芯)                 |                         |
| Type of clamp(线夹类型)             |                         |
| Cable diameter(电缆直径)            |                         |