


| Main technical indicators(主要技术指标) |                                                                                                                   |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------|
| 1.Mating (插拔次数)                   | 5000                                                                                                              |
| 2.Working Temperature (温度)        | -55~+150 ℃                                                                                                        |
| 3.IP Rating (防护级别)                | IP 50                                                                                                             |
| 4.Diameter of socket end(插合端直径)   | φ0.9                                                                                                              |
| 5.Testing Voltage (测试电压)          | 1450V                                                                                                             |
| 6.Working Voltage (工作电压)          | 1000V                                                                                                             |
| 7.Rated Current (额定电流)            | 9A                                                                                                                |
| 8.Shell material(壳体材质)            | Brass (chromium plating) shell and chuck nut/(nickel plating) pin sleeve and middleware/黄铜(镀铬)外壳和夹头螺母/(镀镍)插销套和中间件 |
| 9.Pin Material(插针材料)              | Copper alloy gold plating(铜合金镀金)                                                                                  |
| 10.Insulator material(绝缘体材质)      | PPS                                                                                                               |

| Sum up(总结)                  |                                                                                        |
|-----------------------------|----------------------------------------------------------------------------------------|
| Series(系列)                  | B                                                                                      |
| Shell style/model (外壳样式/型号) | TGG: Straight plug, cable collet and nut for fitting a bend relief直塞、电缆夹头和螺母, 用于安装弯曲凸起 |
| Button (按键)                 | A button(一个按键)                                                                         |
| Termination type (终止类型)     | Male solder(公焊锡)                                                                       |
| Line diameter awg(线材直径)     | 30-22AWG                                                                               |
| Cable diameterφ (电缆直径)      | φ8.3-9.2MM                                                                             |
| Matching parts(配件)          | ZGG.3B.P12.CLL                                                                         |

| Location pin combination(定位销组合) |                                          |               |                         |
|---------------------------------|------------------------------------------|---------------|-------------------------|
| (编号)<br>Nunder                  | Number of<br>positioning pins(定<br>位销数量) | Angle(<br>角度) | Series(系列)-3B           |
| G                               | One(1)                                   |               | (Zero degrees)0°        |
| A                               | Two(2)                                   | A             | Thirty degrees(30°)     |
| B                               | Two(2)                                   |               | Forty-five degrees(45°) |
| C                               | Two(2)                                   |               | Sixty degrees(60°)      |
| D                               | Two(2)                                   | γ             | 95 degrees (95°)        |
| E                               | Two(2)                                   | β             | 120 degrees(120°)       |
| F                               | Two(2)                                   |               | 145 degrees(145°)       |
| J                               | Two(2)                                   | A             | 37.5degrees(37.5°)      |
| K                               | Two(2)                                   |               | 52.5degrees(52.5°)      |
| L                               | Two(2)                                   | γ             | Seventy degrees(70°)    |


|        | A      | B      | C√     | ANGLE   |       |
|--------|--------|--------|--------|---------|-------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1° |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5° |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |       |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |       |




|    | A      | L      | M      | S1     | S2     |
|----|--------|--------|--------|--------|--------|
| MM | φ18    | 57     | 41.5   | 16.0   | 15     |
| in | 0.7087 | 2.2441 | 1.6339 | 0.6299 | 0.5906 |



Welded surface  
(焊接面)



Positive view  
(正视图)



Solder core  
(焊接型公胶芯)

TG G. 3B. P12.C L A D 92 H

Model(型号)

Positioning pin(定位销)

Series(系列)

Needle core configuration(针芯配置)

Outer casing(外壳)

Insulator(绝缘体)

Needle core(针芯)

Type of clamp(线夹类型)

Cable diameter(电缆直径)

SH means a sheath type, not a cover type.  
(H表示护套型, 不表示为不带护套型)

|                                  |  |          |  |                                      |          |                                        |
|----------------------------------|--|----------|--|--------------------------------------|----------|----------------------------------------|
| DESIGNED(设计)                     |  | DATE(日期) |  | SCALE(比例)                            | N/A(不适用) | MODEL TYPE                             |
| CHECKED(校对)                      |  | DATE(日期) |  | VIEW(视图)                             |          | 型号类型: TGG.3B.P12.CLAD92H               |
| APPROVED(审核)                     |  | DATE(日期) |  | UNIT(单位)                             | MM       | PART NO. 3B12-core plug<br>名称: 3B12芯插头 |
| REVISIONS                        |  |          |  | MATERIAL (材料)                        |          | DWG NO.:                               |
| www.helloxkb.com www.helloxkb.cn |  |          |  | XKB INDUSTRIAL PRECISION CO.,LIMITED |          | WEIGHT(重量)                             |
|                                  |  |          |  |                                      |          | SHEET(张)                               |
|                                  |  |          |  |                                      |          | REVISION(修订)                           |
|                                  |  |          |  |                                      |          | 1/1                                    |
|                                  |  |          |  |                                      |          | A0                                     |