


Main technical indicators(主要技术指标)	
1.Mating (插拔次数)	5000
2.Working Temperature (温度)	-55~+150 ℃
3.IP Rating (防护级别)	IP 50
4.Diameter of socket end(插合端直径)	φ1.3
5.Testing Voltage (测试电压)	1750V
6.Working Voltage (工作电压)	1600V
7.Rated Current (额定电流)	14A
8.Shell material(壳体材质)	Brass (chromium plating) shell and chuck nut/(镀铬) 外壳和夹头螺母/ Copper alloy gold plating(铜合金镀金)
9.Pin Material(插针材料)	Copper alloy gold plating(铜合金镀金)
10. Insulator material(绝缘体材质)	PPS

Sum up(总结)	
Series(系列)	B
Shell style/model (外壳样式/型号)	THG: Elbow plug, cable collet/电缆夹头弯头
Button (按键)	A button(一个按键)
Termination type (终止类型)	Male solder(公焊锡)
Line diameter awg(线材直径)	28-20 AWG
Cable diameterφ (电缆直径)	φ4.3-5.2MM
Matching parts(配件)	ZGG.2B.P05.CLL

Location pin combination(定位销组合)			
(编号) Numder	Number of positioning pins(定位销数量)	Angle(角度)	Series(系列)--2B
G	One(1)		(Zero degrees)0°
A	Two(2)	A	Thirty degrees(30°)
B	Two(2)		Forty-five degrees(45°)
C	Two(2)		Sixty degrees(60°)
D	Two(2)	γ	95 degrees (95°)
E	Two(2)	β	120 degrees(120°)
F	Two(2)		145 degrees(145°)
J	Two(2)	A	37.5degrees(37.5°)
K	Two(2)		52.5degrees(52.5°)
L	Two(2)	γ	Seventy degrees(70°)


	A	B	C√	ANGLE	
5-10	±0.02	±0.05	±0.1	0°-30°	±0.1°
50-100	±0.1	±0.15	±0.2	61°-90°	±0.5°
50-100	±0.15	±0.2	±0.25		
100-	±0.15%	±0.20%	±0.25%		




	A	D	H	L	M	S1	S2	S3
MM	16.5	9	34	41.5	29.5	14	12	13
in	0.6496	0.3543	1.3386	1.6339	1.1615	0.5512	0.4725	0.5118



Welded surface
(焊接面)



Solder core
(焊接型公胶芯)



Positive view
(正视图)

TH G. 2B. P05.C L A D 52

Model(型号)	TH G. 2B. P05.C L A D 52
Positioning pin(定位销)	TH G. 2B. P05.C L A D 52
Series(系列)	TH G. 2B. P05.C L A D 52
Needle core configuration(针芯配置)	TH G. 2B. P05.C L A D 52
Outer casing(外壳)	TH G. 2B. P05.C L A D 52
Insulator(绝缘体)	TH G. 2B. P05.C L A D 52
Needle core(针芯)	TH G. 2B. P05.C L A D 52
Type of clamp(线夹类型)	TH G. 2B. P05.C L A D 52
Cable diameter(电缆直径)	TH G. 2B. P05.C L A D 52

DESIGNED(设计)		DATE(日期)		SCALE(比例)	NA(不适用)	MODEL TYPE 型号类型: THG.2B.P05.CLAD.52
CHECKED(校对)		DATE(日期)		VIEW(视图)		PART NO. 2B5-core plug 名称: 2B5芯插头
APPROVED(审核)		DATE(日期)		UNIT(单位)	MM	DWG NO.:
REVISIONS				MATERIAL (材料)		
www.helloxkb.com www.helloxkb.cn				XKB INDUSTRIAL PRECISION CO.,LIMITED		WEIGHT(重量) SHEET(表) REVISION(修订)
						1/1 A0