

## Main technical indicators(主要技术指标)

|                                 |                                                                            |
|---------------------------------|----------------------------------------------------------------------------|
| 1.Mating (插拔次数)                 | 5000                                                                       |
| 2.Working Temperature (温度)      | -55~+150 °C                                                                |
| 3.IP Rating (防护级别)              | IP 50                                                                      |
| 4.Diameter of socket end(插合端直径) | Ø0.7                                                                       |
| 5.Testing Voltage (测试电压)        | 1150V                                                                      |
| 6.Working Voltage (工作电压)        | 1350V                                                                      |
| 7.Rated Current (额定电流)          | 6.5A                                                                       |
| 8.Shell material(壳体材质)          | Brass (chromium plating) shell and chuck nut/(镀铬) 外壳和夹头螺母/<br>(镀铬) 插销套和中间件 |
| 9.Pin Material(插针材料)            | Copper alloy gold plating(铜合金镀金)                                           |
| 10.Insulator material(绝缘体材质)    | PPS                                                                        |


## Sum up(总结)

|                             |                                       |
|-----------------------------|---------------------------------------|
| Series(系列)                  | B                                     |
| Shell style/model (外壳样式/型号) | THG: Elbow plug, cable collet/ 电缆夹头弯头 |
| Button (按键)                 | A button(一个按键)                        |
| Termination type (终止类型)     | Male solder(公焊锡)                      |
| Line diameter awg(线材直径)     | 30-22AWG                              |
| Cable diameterφ (电缆直径)      | Ø4.3-5.2MM                            |
| Matching parts(配件)          | ZGG.2B.P14.CLL                        |



## Location pin combination (定位销组合)

| (编号)<br>Number | Number of<br>positioning pins(定<br>位销数量) | Angle(<br>角度) | Series(系列)-2B              |
|----------------|------------------------------------------|---------------|----------------------------|
| G              | One(1)                                   |               | (Zero degrees)0°           |
| A              | Two(2)                                   | A             | Thirty degrees(30°)        |
| B              | Two(2)                                   |               | Forty-five<br>degrees(45°) |
| C              | Two(2)                                   |               | Sixty degrees(60°)         |
| D              | Two(2)                                   | Y             | 95 degrees (95°)           |
| E              | Two(2)                                   | β             | 120 degrees(120°)          |
| F              | Two(2)                                   |               | 145 degrees(145°)          |
| J              | Two(2)                                   | A             | 37.5degrees(37.5°)         |
| K              | Two(2)                                   |               | 52.5degrees(52.5°)         |
| L              | Two(2)                                   | Y             | Seventy degrees(70°)       |

|        | A      | B      | C/     | ANGLE   |       |
|--------|--------|--------|--------|---------|-------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1° |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5° |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |       |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |       |



|    | A      | D      | H      | L      | M      | S1     | S2     | S3     |
|----|--------|--------|--------|--------|--------|--------|--------|--------|
| MM | 16.5   | 9      | 34     | 41.5   | 29.5   | 14     | 12     | 13     |
| in | 0.6496 | 0.3543 | 1.3386 | 1.6339 | 1.1615 | 0.5512 | 0.4725 | 0.5118 |

Welded surface  
(焊接面)Positive view  
(正视图)Solder core  
(焊接型公胶芯)

TH G. 2B. P14.C L A D 52

Model(型号)

Positioning pin(定位销)

Series(系列)

Needle core configuration(针芯配置)

Outer casing(外壳)

Insulator(绝缘体)

Needle core(针芯)

Type of clamp(线夹类型)

Cable diameter(电缆直径)

|                                  |          |                                      |          |                                        |
|----------------------------------|----------|--------------------------------------|----------|----------------------------------------|
| DESIGNED (设计)                    | DATE(日期) | SCALE(比例)                            | N/A(不适用) | MODEL TYPE<br>型号类型: THG.2B.P14.CLAD.52 |
| CHECKED (校对)                     | DATE(日期) | VIEW(视图)                             |          | PART NO. 2B14-core plug<br>名称: 2B14芯插头 |
| APPROVED (审核)                    | DATE(日期) | UNIT(单位)                             | MM       | DWG NO.:                               |
| REVISIONS                        |          | MATERIAL (材料)                        |          | WEIGHT(重量) SHEET(页) REVISION(修订)       |
| www.hellokxb.com www.hellokxb.cn |          | XKB INDUSTRIAL PRECISION CO.,LIMITED |          | 1/1 A0                                 |