


1.View and size(视图及尺寸)

Main technical indicators(主要技术指标)	
1.Mating (插拔次数)	5000
2.Working Temperature (温度)	-55~+150 ℃
3.IP Rating (防护级别)	IP 50
4.Diameter of socket end(插合端直径)	$\frac{2.3}{0.2}$ mm
5.Vtest (AC) /测试电压(交流)	$\frac{1500}{1500}$ V
6.Vtest (DC) /测试电压(直流)	$\frac{2100}{2100}$ V
7.Rated Current (额定电流)	$\frac{10}{7}$ A
8.Shell material(壳体材质)	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces /黄铜 (镀铬) 外壳和夹头螺母, 镀镍黄铜锁套和中间件
9.Pin Material(插针材料)	Copper alloy gold plating(铜合金镀金)
10.Insulator material(绝缘体材质)	PPS


Sum up(总结)	
Series(系列)	S
Shell style/model (外壳样式/型号)	TLA: Elbow plug, cable collet/弯头插头、电缆夹头
Button (按键)	Hermaphroditic keying (half moon insert) with male pin 1/带公销1的公母键控 (半月形插入)
Termination type (终止类型)	Male solder(公焊锡)
Line diameter awg(线材直径)	30AWG-22AWG
Cable diameter ϕ (电缆直径)	ϕ 2.3-3.2MM
Matching parts(配套零件)	ZRA.1S.P05.CLL

Sum up(总结)	
Humidity (max)/湿度最大	<=95% [at 60 deg C /140 F] /<=95%[在60摄氏度/140摄氏度时]
Vibration/震动	15g [10 Hz - 2000 Hz]
Shock Resistance/抗冲击性	100 g [6 ms]
Climatical Category /气候类别	50/175/21
Salt Spray Corrosion/盐雾测试	>48 hr />48小时

	A	B	C $\sqrt$	ANGLE	
5-10	$\pm$ 0.02	$\pm$ 0.05	$\pm$ 0.1	0°-30°	$\pm$ 0.1°
50-100	$\pm$ 0.1	$\pm$ 0.15	$\pm$ 0.2	61°-90°	$\pm$ 0.5°
50-100	$\pm$ 0.15	$\pm$ 0.2	$\pm$ 0.25		
100-	$\pm$ 0.15%	$\pm$ 0.20%	$\pm$ 0.25%		



	A	L	M	H	S2
MM	16	26.5	15.5	28.5	8.5
in	0.63	1.04	0.61	1.12	0.33



Welded surface
(焊接面)



Solder core
(焊接型公胶芯)

Model(型号) TLA. 1S. P05.C L A C 32
Series(系列) TL
Needle core configuration(针芯配置) 1S
Outer casing(外壳) P05
Insulator(绝缘体) C
Needle core(针芯) L
Type of clamp(线夹类型) A
Cable diameter(电缆直径) C 32

DESIGNED (设计)		DATE(日期)		SCALE(比例)	N/A(不适用)	MODEL TYPE 型号类型: TLA.1S.P05.CLAC.32
CHECKED (校对)		DATE(日期)		VIEW(视图)		PART NO. 1S5-core plug 名称: 1S5芯插头
APPROVED (审核)		DATE(日期)		UNIT(单位)	MM	DWG NO.:
REVISIONS			MATERIAL (材料)			
www.helloxkb.com www.helloxkb.cn			XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT(重量) SHEET(表) REVISION(修订)
						1/1 A0