


## 1.View and size(视图及尺寸)

| Main technical indicators(主要技术指标) |                                                                               |
|-----------------------------------|-------------------------------------------------------------------------------|
| 1.Mating (插拔次数)                   | 5000                                                                          |
| 2.Working Temperature (温度)        | -55~+150 °C                                                                   |
| 3.IP Rating (防护级别)                | IP 50                                                                         |
| 4.Diameter of socket end(插合端直径)   | ∅0.7                                                                          |
| 5.Testing Voltage (测试电压)          | 950V                                                                          |
| 6.Working Voltage (工作电压)          | 700V                                                                          |
| 7.Rated Current (额定电流)            | 4.0A                                                                          |
| 8.Shell material(壳体材质)            | Brass (chromium plating)/(nickel plating) fixation ring/<br>黄铜 (镀铬) /(镀镍) 固定圈 |
| 9.Pin Material(插针材料)              | Copper alloy gold plating(铜合金镀金)                                              |
| 10.Insulator material(绝缘体材质)      | PPS                                                                           |


| Sum up(总结)                  |                                                       |
|-----------------------------|-------------------------------------------------------|
| Series(系列)                  | B                                                     |
| Shell style/model (外壳样式/型号) | ZCG:With two nuts (fixed back and forth)带有两个螺母 (前后固定) |
| Button (按键)                 | A button(一个按键)                                        |
| Termination type (终止类型)     | Mother solder tin(母焊锡)                                |
| Line diameter awg(线材直径)     | 30-22AWG                                              |
| Cable diameter∅ (电缆直径)      | 0-0                                                   |
| Match plug(匹配插头)            | TGG.3B.P26.CLAD92H                                    |

| Location pin combination(定位销组合) |                                      |           |                         |
|---------------------------------|--------------------------------------|-----------|-------------------------|
| (编号)<br>Number                  | Number of<br>positioning pins(定位销数量) | Angle(角度) | Series(系列)-3B           |
| G                               | One(1)                               |           | (Zero degrees)0°        |
| A                               | Two(2)                               | A         | Thirty degrees(30°)     |
| B                               | Two(2)                               |           | Forty-five degrees(45°) |
| C                               | Two(2)                               |           | Sixty degrees(60°)      |
| D                               | Two(2)                               | γ         | 95 degrees (95°)        |
| E                               | Two(2)                               | β         | 120 degrees(120°)       |
| F                               | Two(2)                               |           | 145 degrees(145°)       |
| J                               | Two(2)                               | A         | 37.5degrees(37.5°)      |
| K                               | Two(2)                               |           | 52.5degrees(52.5°)      |
| L                               | Two(2)                               | γ         | Seventy degrees(70°)    |


|        | A      | B      | C√     | ANGLE   |       |
|--------|--------|--------|--------|---------|-------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1° |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5° |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |       |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |       |




|    | A    | L    | E     | M    | S1   | S2   |
|----|------|------|-------|------|------|------|
| MM | ∅24  | 22   | M18*1 | 4.5  | 16.5 | 22   |
| in | 0.94 | 0.87 |       | 0.18 | 0.65 | 0.87 |




Welded surface  
(焊接面)



Panel hole size  
(面板开孔尺寸)



(Welded mother  
adhesive core)  
焊接型母胶芯



Positive view of the socket  
(插座正视图)

Model(型号) ZC G.3B.P26.C L L  
Positioning pin(定位销)  
Series(系列)  
Needle core configuration(针芯配置)  
Outer casing(外壳)  
Insulator(绝缘体)  
Needle core(针芯)

|                                  |  |          |                                      |               |          |                                            |
|----------------------------------|--|----------|--------------------------------------|---------------|----------|--------------------------------------------|
| DESIGNED(设计)                     |  | DATE(日期) |                                      | SCALE(比例)     | N/A(不适用) | MODEL TYPE<br>型号类型: ZCG.3B.P26.CLL         |
| CHECKED(校对)                      |  | DATE(日期) |                                      | VIEW(视图)      |          | PART NO. 3B26 core socket<br>名称: 3B26芯插座   |
| APPROVED(审核)                     |  | DATE(日期) |                                      | UNIT(单位)      | MM       | DWG NO.:                                   |
| REVISIONS                        |  |          |                                      | MATERIAL (材料) |          |                                            |
| www.helloxkb.com www.helloxkb.cn |  |          | XKB INDUSTRIAL PRECISION CO.,LIMITED |               |          | WEIGHT(重量) SHEET(表) REVISION(修订)<br>1/1 A0 |