


1.View and size(视图及尺寸)

Main technical indicators(主要技术指标)	
1.Mating (插拔次数)	5000
2.Working Temperature (温度)	-55~+150 ℃
3.IP Rating (防护级别)	IP 50
4.Diameter of socket end(插合端直径)	ø0.7MM
5.Vtest (AC) /测试电压(交流)	1000V
6.Vtest (DC) /测试电压(直流)	1500V
7.Rated Current (额定电流)	7A
8.Shell material(壳体材质)	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces /黄铜（镀铬）外壳和夹头螺母，镀镍黄铜锁套和中间件
9.Pin Material(插针材料)	Copper alloy gold plating(铜合金镀金)
10.Insulator material(绝缘体材质)	PPS


Sum up(总结)	
Series(系列)	B
Shell style/model（外壳样式/型号）	ZRA: Fixed receptacle, nut fixing/固定插座，螺母固定
Button（按键）	Hermaphroditic keying (half moon insert) with female pin 1/雌雄同体键控（半月形插入），带母销1
Termination type（终止类型）	Female print PCB(印刷PCB)
Line diameter awg(线材直径)	32AWG-24AWG
Cable diameterø（电缆直径）	-
Match plug(匹配插头)	TFA.0S.P04.CLAD32

Sum up(总结)	
Humidity (max)/湿度最大	<=95% [at 60 deg C /140 F] / <=95%[在60摄氏度/140摄氏度时]
Vibration/震动	15g [10 Hz - 2000 Hz]
Shock Resistance/抗冲击性	100 g [6 ms]
Climatical Category /气候类别	50/175/21
Salt Spray Corrosion/盐雾测试	>48 hr />48小时


	A	B	C√	ANGLE	
5-10	±0.02	±0.05	±0.1	0°-30°	±0.1°
50-100	±0.1	±0.15	±0.2	61°-90°	±0.5°
50-100	±0.15	±0.2	±0.25		
100-	±0.15%	±0.20%	±0.25%		



	A	L	E	S1	S2
MM	ø10	18.5	M9*0.6	8.2	11
in	0.39	0.73		0.32	0.43



Pane hole size
(面板开孔尺寸)



Pcb plate opening size
(PCB板开孔尺寸)





Plate joint master rubber core
(板接型母胶芯)



Welded surface
(焊接面)

Model(型号)	ZRA.0S.P04.C L N
Series(系列)	
Needle core configuration(针芯配置)	
Outer casing(外壳)	
Insulator(绝缘体)	
Needle core(针芯)	

DESIGNED (设计)		DATE(日期)		SCALE(比额)	N/A(不适用)	MODEL TYPE 型号类型: ZRA.0S.P04.CLN
CHECKED (校对)		DATE(日期)		VIEW(视图)		PART NO. 0S4-core socket 名称: 0S4芯插座
APPROVED (审核)		DATE(日期)		UNIT(单位)	MM	DWG NO.:
REVISIONS				MATERIAL (材料)		
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn				XKB INDUSTRIAL PRECISION CO.,LIMITED		WEIGHT(重量) SHEET(表) REVISION(修订)
						1/1 A0